

W1G130-AA49-01

EC axial compact fan - ESM



ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

sales@fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

Nominal data

| | | | |
|--------------------------|-------------------|-------|-------|
| Type | W1G130-AA49-01 | | |
| Motor | M1G055-AI | | |
| Phase | | 1~ | 1~ |
| Nominal voltage | VAC | 115 | 115 |
| Frequency | Hz | 50/60 | 50/60 |
| Type of data definition | | ml | ml |
| Speed (rpm) | min ⁻¹ | 2800 | 3200 |
| Power input | W | 15 | 24 |
| Current draw | A | 0.24 | 0.38 |
| Max. back pressure | Pa | | 90 |
| Min. ambient temperature | °C | -30 | -30 |
| Max. ambient temperature | °C | 60 | 60 |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations




Technical features

| | |
|--|---|
| Mass | 0.75 kg |
| Size | 130 mm |
| Motor size | 55 |
| Material of blades | PA plastic |
| Material of wall ring | PP plastic |
| Number of blades | 7 |
| Direction of air flow | V |
| Direction of rotation | Counter-clockwise, seen on rotor |
| Type of protection | IP55 |
| Insulation class | "B" |
| Humidity (F) / environmental protection class (H) | H1+ |
| Max. permissible ambient motor temp. (transp./ storage) | + 80 °C |
| Min. permissible ambient motor temp. (transp./storage) | - 40 °C |
| Mounting position | Any |
| Condensation drainage holes | None |
| Operation mode | S1 |
| Motor bearing | Ball bearing |
| Technical features | - Speed selection max/min - Soft start - Over-temperature protected motor |
| Speed steps | 2 |
| EMC interference immunity | Acc. to EN 61000-6-2 (industrial environment) |
| EMC interference emission | Acc. to EN 61000-6-3 (household environment) |
| Motor protection | Thermal overload protector (TOP) wired internally |
| Cable exit | Lateral |
| Protection class | II |
| Product conforming to standard | EN 60335-1; EN 60335-2-24; EN 60335-2-80; EN 60335-2-89; CE |
| Approval | VDE; CSA C22.2 no. 77 + CAN/CSA-E60730-1; EAC; UL 1004-3 + 60730-1 |




Product drawing




- 1 Direction of air flow "V"
- 2 Connection line AWG20, 3 x brass lead tips crimped
- 3 Preferably use 2x Remform screws WN-156-2 5.0x16 Torx galvanised (Arnold). Alternatively use 2x metric M4 screw, mounting provided with nut

Connection screen



Charts: Air flow 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-152097-1
Measurement: LU-152098-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L_{wA} measured as per ISO 13347 / L_{pA} measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

| | U | f | n | P _{ed} | I | L _{pA_{in}} | L _{wA_{in}} | q _v | P _{fs} | q _v | P _{fs} |
|---|-----|----|-------------------|-----------------|------|------------------------------|------------------------------|-------------------|-----------------|----------------|-----------------|
| | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | m ³ /h | Pa | cfm | in. wg |
| 1 | 115 | 60 | 3200 | 23 | 0.35 | 55 | 63 | 365 | 0 | 215 | 0.00 |
| 2 | 115 | 60 | 3200 | 23 | 0.35 | 55 | 63 | 330 | 30 | 195 | 0.12 |
| 3 | 115 | 60 | 3200 | 24 | 0.37 | 54 | 61 | 285 | 60 | 170 | 0.24 |
| 4 | 115 | 60 | 3200 | 24 | 0.38 | 55 | 62 | 230 | 90 | 135 | 0.36 |
| 5 | 115 | 60 | 2800 | 15 | 0.24 | 54 | 61 | 315 | 0 | 185 | 0.00 |
| 6 | 115 | 60 | 2800 | 16 | 0.24 | 54 | 61 | 290 | 24 | 170 | 0.10 |
| 7 | 115 | 60 | 2800 | 16 | 0.25 | 54 | 61 | 250 | 46 | 150 | 0.18 |
| 8 | 115 | 60 | 2800 | 16 | 0.24 | 54 | 61 | 200 | 70 | 115 | 0.28 |

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · L_{pA_{in}} = Sound pressure level inlet side · L_{wA_{in}} = Sound power level inlet side · q_v = Air flow
P_{fs} = Pressure increase

